

FIBKV02

WORKS IN WET ENVIRONMENT

Water-repellent mechanical leather glove with Kevlar lining for high durability, ideal for electric arcing



Certifications and norms





EN 388 3 2 4 3 B



EN 407 41×1××

Risk Protection







Specific benefits



Performance

• The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)

Applications

- Agriculture
- Public Works
- Building
- Maintenance
- Cleanliness
- Temporary Work



FIBKV02

WORKS IN WET ENVIRONMENT

Water-repellent mechanical leather glove with Kevlar lining for high durability, ideal for electric arcing

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE 2 [0-5] CUT RESISTANCE 4 [0-4] TEAR RESISTANCE 3 [0-4] PIERCE RESISTANCE B [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Cut and sewn leather palm / leather back
Mechanical Glove Type	Cut Sewn
Leather Treatment	Hydro
Thickness (mm)	1,0 -> 1,2
Cuff caracteristic	Sewn open cuff with elastic
Benefits element	Repellent
Color	Beige
Size	8, 9, 10







FIBKV02

WORKS IN WET ENVIRONMENT

Water-repellent mechanical leather glove with Kevlar lining for high durability, ideal for electric arcing

Logistics information											
Reference	Colour	Size	Designation	EAN13	Box code		Å	Weight			
FIBKV0210	Beige	10	FIBKV02	3295249048532	13295249048539	60	12	4.0 kg	60.0 cm	28.0 cm	24.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height