



Hand protection

TIG15K

THERMAL WELDING WORKS

Thermal leather glove, combining great flexibility and finesse for welding work in heavy industry



Specific benefits



Performance

· The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)

Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Maintenance
- Automotive
- Temporary work

Certifications and norms



EN 388
2111X

EN 12477
TYPE B



EN 407
41XX4X



Hand protection

TIG15K

THERMAL WELDING WORKS

Thermal leather glove, combining great flexibility and finesse for welding work in heavy industry

Standards - Details



EN388:2016+A1:2018

2 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
1 [0-4] TEAR RESISTANCE
1 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Special glove
Glove family	Cut and sewn leather palm / leather back
Mechanical glove kind	Cut and sewn
Special gloves kind	Welding
Thickness	0,8 -> 1,0 mm
Arm level protection	Forearm cuff (< 400mm)
Cuff characteristic	Leather cuff
Cuff length	150 mm
Color	Grey
Size	8, 9, 10








Safety gloves

TIG15K

THERMAL WELDING WORKS

Thermal leather glove, combining great flexibility and finesse for welding work in heavy industry

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TIG15K08	Grey	08	TIG15K	3295249033965	13295249033962	36	6	4.9 kg	34.8 cm	42.2 cm	16.8 cm
TIG15K09	Grey	09	TIG15K	3295249033972	13295249033979	36	6	5.8 kg	36.4 cm	44.0 cm	19.0 cm
TIG15K10	Grey	10	TIG15K	3295249033989	13295249033986	36	6	6.5 kg	36.4 cm	46.2 cm	19.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height