



手部防护

TIG15K

热焊工作

Thermal leather glove, combining great flexibility and finesse for welding work in heavy industry



具体优势

 高性能

· 高性能HEATnocut纤维使其具备高温耐接触性 (100°C可持续15秒)

应用行业

- 公共工程
- 建筑业
- 终饰工程/工艺
- 维修业
- 汽车业
- 临时作业

标准和认证



EN 388
2111X

EN 12477

类型B



EN 407
41XX4X



手部防护

TIG15K

热焊工作

Thermal leather glove, combining great flexibility and finesse for welding work in heavy industry

详细信息 - 标准



EN388:2016+A1:2018

2 [0-4] 耐磨

1 [0-5] 防切割

1 [0-4] TEAR RESISTANCE

1 [0-4] PIERCE RESISTANCE

X [A-F] CUT RESISTANCE ISO 13997

技术细节

手套类别	特殊手套
手套类别	裁切缝合的皮革掌面/皮革掌背
机械手套类	裁剪及缝纫
特殊手套类型	电焊
厚度	0,8 -> 1,0 mm
手臂保护	前臂袖口 (< 400mm)
袖口特征	皮革袖口
Cuff length	150 mm
颜色	灰色
尺码	8, 9, 10








Safety gloves

TIG15K

THERMAL WELDING WORKS

Thermal leather glove, combining great flexibility and finesse for welding work in heavy industry

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TIG15K08	Grey	08	TIG15K	3295249033965	13295249033962	36	6	4.9 kg	34.8 cm	42.2 cm	16.8 cm
TIG15K09	Grey	09	TIG15K	3295249033972	13295249033979	36	6	5.8 kg	36.4 cm	44.0 cm	19.0 cm
TIG15K10	Grey	10	TIG15K	3295249033989	13295249033986	36	6	6.5 kg	36.4 cm	46.2 cm	19.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height