



VENICUTD05

长时间正常切割作业

手部防护



具体优势



耐用性

· 无溶剂涂层，环保



易用性

· 可触屏，用户在使用平板电脑或智能手机时，无需摘下手套



卫生环保

· 无硅/无乳胶/无DMF，降低过敏风险且不会在接触物上留下痕迹



高性能

· 重量非常轻，使其具备最佳的灵巧性

· 聚氨酯涂层的防滑性能提供了良好的抓握力。

· 高抗静电性能，减少电火花风险

标准和认证



EN 388
3 X 4 1 D



EN 16350



EN 407
X 1 X X X X

ANSI ISEA 105

A4

技术与标签

· 无溶剂



无DMF



无硅

应用行业

- 公共工程
- 建筑业
- 终饰工程/工艺
- 维修业
- 汽车业
- 采矿

防范风险



抗静电



高温



切割



磨损



enjoy safety.



VENICUTD05

长时间正常切割作业

手部防护

详细信息 - 标准



EN388:2016+A1:2018

3 [0-4] 耐磨

X [0-5] 防切割

4 [0-4] TEAR RESISTANCE

1 [0-4] PIERCE RESISTANCE

D [A-F] CUT RESISTANCE ISO 13997

技术细节

手套类别	机械防护手套
手套类别	针织涂层手套
机械手套类	针织
涂层材质及饰面	PU涂层
涂层水平	掌面涂层
涂层数	单涂层
针数	18
产品优势	静电耗散, 触摸感应, Reach, 供应商包装
颜色	黑色
尺码	6, 7, 8, 9, 10, 11
包装类型	独立包装








Safety gloves

VENICUTD05

LONG-LASTING CUT WORK

Level D cut-resistant glove with electrostatic properties and very good finesse of work, ideal in dry conditions

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VECUTD05NO06	Black	06	VENICUTD05	3295249264246	13295249264243	60	12	4.2 kg	35.2 cm	64.6 cm	16.6 cm
VECUTD05NO07	Black	07	VENICUTD05	3295249264277	13295249264274	60	12	7.0 kg	33.0 cm	65.0 cm	15.0 cm
VECUTD05NO08	Black	08	VENICUTD05	3295249264284	13295249264281	60	12	4.7 kg	35.4 cm	64.2 cm	16.8 cm
VECUTD05NO09	Black	09	VENICUTD05	3295249264291	13295249264298	60	12	7.6 kg	16.4 cm	34.2 cm	65.0 cm
VECUTD05NO10	Black	10	VENICUTD05	3295249264307	13295249264304	60	12	7.9 kg	16.0 cm	35.0 cm	64.6 cm
VECUTD05NO11	Black	11	VENICUTD05	3295249264314	13295249264311	60	12	8.0 kg	16.0 cm	35.8 cm	64.6 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height