

VE726

WORKS IN OILY ENVIRONMENT

Mechanical glove with good flexibility for working in oily conditions



Certifications and norms





EN 388 3121X

Risk Protection





Specific benefits



Hygiene

· Nitrile means no risk of allergies for users



Performance

·The nitrile coating gives people working in oily/greasy environments an excellent grip on the objects they handle

Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Automotive
- Water and Waste Treatment



VE726

WORKS IN OILY ENVIRONMENT

Mechanical glove with good flexibility for working in oily conditions

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE 1 [0-5] CUT RESISTANCE 2 [0-4] TEAR RESISTANCE 1 [0-4] PIERCE RESISTANCE X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Knitted coated glove
Mechanical Glove Type	Tricot
Coating material and finition	Smooth Aqua Polymer
Coating Level	Palm Coating
Number of Coatings	Single Coated
Gauge	15
Color	Gray-Black
Size	7, 8, 9, 10, 11
Type of conditioning	in individual bags







VE726

WORKS IN OILY ENVIRONMENT

Mechanical glove with good flexibility for working in oily conditions

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code		Å	Weight			
VE726NO07	Grey-Black	07	VE726	3295249178185	13295249178182	120	12	5.1 kg	29.0 cm	43.0 cm	32.0 cm
VE726NO08	Grey-Black	08	VE726	3295249178192	13295249178199	120	12	5.6 kg	28.8 cm	43.2 cm	32.4 cm
VE726NO09	Grey-Black	09	VE726	3295249178208	13295249178205	120	12	8.5 kg	31.4 cm	70.6 cm	24.4 cm
VE726NO10	Grey-Black	10	VE726	3295249178215	13295249178212	120	12	6.7 kg	29.0 cm	43.2 cm	32.2 cm
VE726NO11	Grey-Black	11	VE726	3295249198022	13295249198029	120	12	7.0 kg	29.4 cm	43.0 cm	33.4 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height



