



TERK500 XTREM HEAT

TERMAL ÖZEL ÇALIŞMALAR

El Koruma



Avantajlar



Performans

· Yüksek performanslı HEATnocut fiber, temas ısısına karşı direnç sağlar (15 saniye boyunca 500°C)

Uygulamalar

- Yapı
- İkinci iş / Zanaatkarlar
- Hafif sanayi
- Bakım
- İlaç Endüstrisi / Laboratuvarlar
- Otomotiv

Sertifikalar ve standartlar



EN 388
2 5 4 4 E



EN 407
4 4 4 2 4 X

Karşı korur



Isı



Kesme



enjoy safety.

edit 21/11/2024
www.deltaplus.eu



TERK500 XTREM HEAT

TERMAL ÖZEL ÇALIŞMALAR

El Koruma

Detaylar - Standartlar



EN388:2016+A1:2018

2 [0-4] AŞINMA DİRENCİ
5 [0-5] KESİLME DİRENCİ
4 [0-4] TEAR RESİSTANCE
4 [0-4] PIERCE RESİSTANCE
E [A-F] CUT RESİSTANCE ISO 13997

Ürün bilgileri

Eldiven tipi	Mekanik eldiven
Eldiven ailesi	Kesilmiş ve dikilmiş eldiven, kumaş avuç içi / kumaş sırt
Mekanik eldiven tipi	Kesik dikilmiş
Kol koruma seviyesi	Uzunluk: Önkol (< 400mm)
Manşet özelliği	Güvenlik manşeti
Cuff length (mm)	160
Renk	Sarı
Boyutlar	Tek
Paketleme tipi	bireysel çantada








Safety gloves

TERK500 XTREM HEAT

THERMAL SPECIFIC WORKS

Level E cut-resistant reinforced thermal glove, ideal for extreme heat environments

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TERK500	Yellow	One size	TERK500 XTREM HEAT	3295249228668	13295249228665	36	1	15.8 kg	50.0 cm	50.0 cm	50.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height