



Protezione delle mani

PM160

LAVORI IN AMBIENTE ASCIUTTO

Guanto meccanico, puntinato per una miglior destrezza



Benefici

Prestazioni

· Leggeri per una destrezza ottimale

Campi di utilizzo

- Finitura / artigiani
- Manutenzione
- Automotive
- Lavoro temporaneo
- Stoccaggio

Certificazioni e norme



EN 388
214XX

Protegge contro i rischi



Usura



PM160

LAVORI IN AMBIENTE ASCIUTTO

Guanto meccanico, puntinato per una miglior destrezza

Protezione delle mani

Dettagli - Norme



EN388:2016+A1:2018

2 [0-4] RESISTENZA ALL'ABRASIONE
1 [0-5] RESISTENZA AL TAGLIO
4 [0-4] TEAR RESISTANCE
X [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Dettagli tecnici

Tipo di guanto	Guanto meccanico
Gamma di guanti	Guanto in maglia non spalmato puntinato
Tipo di guanto meccanico	Lavorazione a maglia
Materiale della puntinatura	Puntini in PVC
Finezza	13
Vantaggio supplementare	Reach
Colore	Bianco
Taglia	7, 9








Safety gloves

PM160

WORKS IN DRY ENVIRONMENT

Mechanical glove, with studs for a better grip

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
PM16007	White	07	PM160	3295249035440	13295249035447	300	12	13.8 kg	27.8 cm	61.0 cm	45.8 cm
PM16009	White	09	PM160	3295249035457	13295249035454	300	12	15.8 kg	46.0 cm	62.6 cm	27.2 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height