



Protezione delle mani

DS202RP

LAVORI IN AMBIENTE ASCIUTTO

Guanto per protezione meccanica Docker, rinforzato su palmo, pollice e indice per una protezione completa della mano.



Campi di utilizzo

- Lavori pubblici
- Edificio
- Manutenzione
- Lavoro temporaneo
- Trattamento dei rifiuti e delle acque
- Stoccaggio

Certificazioni e norme



EN 388
4 2 2 3 X

Protegge contro i rischi



Usura



Perforazione



Protezione delle mani

DS202RP

LAVORI IN AMBIENTE ASCIUTTO

Guanto per protezione meccanica Docker, rinforzato su palmo, pollice e indice per una protezione completa della mano.

Dettagli - Norme



EN388:2016+A1:2018

4 [0-4] RESISTENZA ALL'ABRASIONE
2 [0-5] RESISTENZA AL TAGLIO
2 [0-4] TEAR RESISTANCE
3 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Dettagli tecnici

Tipo di guanto	Guanto meccanico
Gamma di guanti	Guanto tagliato e cucito, palmo in pelle/dorso in tessuto
Tipo di guanto meccanico	Tagliato e cucito
Materiale della fodera	Pelle, Tessuto di cotone
Spessore (mm)	0,9 -> 1,1
Caratteristica del polsino	Manicotto di sicurezza
Colore	Grigio-Blu
Taglia	10



Safety gloves

DS202RP

WORKS IN DRY ENVIRONMENT

Docker's mechanical glove with palm, thumb and index finger reinforcement, offering full hand protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
DS202RP10	Grey-Blue	10	DS202RP	3295249012908	13295249012905	120	12	27.12 kg	44.0 cm	28.0 cm	68.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height