



Head protection

# ASO2 CLEAR

## SAFETY GLASSES

Clear-lens safety glasses with adjustable nose bridge and bi-material arms for comfort



### Specific benefits



#### Comfort

- Flex temples for an optimal comfort with less pressure
- Soft & flex nose bridge for a better comfort in an extended period of use



#### Easy to use

- Anti-slip ends for an increased comfort and very good hold on the head (or on a helmet)



#### Durability

- Anti-scratch coating increasing lifespan



#### Compatibility

- Extra flat temples for optimal comfort with Ear muffs

### Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Transportation
- Storage

### Certifications and norms



#### EN170

UV 2C - 1.2

#### EN166

1 FT KN / FT

#### ANSI-ISEA Z87.1 - IMPACT

Z87+ U6

### Risk Protection



Shock



UV / IR



Head protection

# ASO2 CLEAR

## SAFETY GLASSES

Clear-lens safety glasses with adjustable nose bridge and bi-material arms for comfort

### Standards - Details

### Technical details

Type of eye protection	Glasses
Use	Inside
Lens Material	Polycarbonate
Lens treatment	Fog (N), Anti-scratch (K)
Lens based curve	9.5
Glasses Style	Dual Lens
Lens color	Clear
Optical class	1
Lens protection class	1.2
Glasses Characteristics	Curved
Mechanical strength (lens)	F, T
Nose pad material	TPR (Thermoplastic Rubber)
Frame Material	Polycarbonate, TPR
Frame Support	Temples
Mechanical strength (frame)	F, T
Temples confort	Non-slip temples, Flexible tip
Accessory included	Strap
Weight (g)	28
Benefits elements	Color perception








Head protection

# ASO2 CLEAR

## SAFETY GLASSES

Clear-lens safety glasses with adjustable nose bridge and bi-material arms for comfort

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ASO2IN	Clear	-	ASO2 CLEAR	3295249228224	13295249228221	100	10	7.6 kg	35.0 cm	70.0 cm	36.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height