



Head protection

# ASO2 SMOKE

## SAFETY GLASSES

Very comfortable smoked-lens safety glasses with adjustable nose bridge and bi-material arms



### Specific benefits



#### Comfort

- Flex temples for an optimal comfort with less pressure
- Soft & flex nose bridge for a better comfort in an extended period of use



#### Easy to use

- Anti-slip ends for an increased comfort and very good hold on the head (or on a helmet)



#### Durability

- Anti-scratch coating increasing lifespan



#### Compatibility

- Extra flat temples for optimal comfort with Ear muffs

### Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Power Energy

### Certifications and norms



#### EN172

UV 5 - 2.5

#### EN166

1 FT KN / FT

#### ANSI-ISEA Z87.1 - IMPACT

Z87+ U6 L2.5

### Risk Protection



Shock



UV / IR



Head protection

# ASO2 SMOKE

## SAFETY GLASSES

Very comfortable smoked-lens safety glasses with adjustable nose bridge and bi-material arms

### Standards - Details

### Technical details

Type of eye protection	Glasses
Use	Outside
Lens Material	Polycarbonate
Lens treatment	Fog (N), Anti-scratch (K)
Lens based curve	9.5
Glasses Style	Dual Lens
Lens color	Smoke
Optical class	1
Lens protection class	2.5
Glasses Characteristics	Curved
Mechanical strength (lens)	F, T
Nose pad material	TPR (Thermoplastic Rubber)
Frame Material	Polycarbonate, TPR
Frame Support	Temples
Mechanical strength (frame)	F, T
Temples confort	Non-slip temples
Accessory included	Strap
Weight (g)	28
Benefits elements	Ear protection compatibility








Head protection

# ASO2 SMOKE

## SAFETY GLASSES

Very comfortable smoked-lens safety glasses with adjustable nose bridge and bi-material arms

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ASO2FU	Smoke	-	ASO2 SMOKE	3295249228217	13295249228214	100	10	8.3 kg	35.0 cm	70.0 cm	36.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height