



MAXIBLOC AN10015T

ANTICHUTE À RAPPEL AUTOMATIQUE

Fall protection



Specific benefits



Performance

· Certification above the maximum rated load of 100 kg: product certified at 150 kg

Applications

- Stavba
- Second work / craftman

Certifications and norms



EN360

RFU 11.062
150 KG

Protects against risks



Fall



MAXIBLOC AN10015T

ANTICHUTE À RAPPEL AUTOMATIQUE

Fall protection

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Galvanized steel
ARA lenght (m)	15
ARA lenght (inch)	590.5515
Cable diameter (mm)	4
Color	Črna
Connector (user side)	Small hook, steel, opening 21 mm
SIZE	15 m
Benefits element	Fall indicator
Lifespan from manufacturing (let)	20
Weight (kg)	4,5
Maximum load for one person (kg)	150
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface








Fall protection

MAXIBLOC AN10015T

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 15 metres

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN10015T	Black	15 m	MAXIBLOC AN10015T	3295249254872	13295249254879	1	1	6.0 kg	21.6 cm	34.0 cm	10.4 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height