



Fall protection

MAXIBLOC AN10010T2

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 10 metres



Specific benefits



Performance

· Certification above the maximum rated load of 100 kg: product certified at 150 kg

Applications

- Building
- Finishing works / Craftsmanship

Certifications and norms



EN360

RFU 11.062
150 KG

Protects against risks



Fall



Fall protection

MAXIBLOC AN10010T2

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 10 metres

Standards - Details

Technical details

| | |
|-------------------------------------|--|
| Type of equipment | Cable reel |
| Composition of the main support | ABS (Acrylonitrile Butadiene Styrene), Galvanized steel |
| ARA length (m) | 10 |
| ARA length (inch) | 393.701 |
| Cable diameter (mm) | 4 |
| Color | Black |
| Connector (user side) | Small hook, steel, opening 21 mm |
| SIZE | 10 m |
| Benefits element | Fall indicator |
| Lifespan from manufacturing (years) | 20 |
| Weight (kg) | 3,75 |
| Maximum load for one person (kg) | 150 |
| Fall arrest work situations | Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface |








Fall protection

MAXIBLOC AN10010T2

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 10 metres

Logistics information

| Reference | Colour | Size | Designation | EAN13 | Box code |  |  | Weight |  |  |  |
|-----------|--------|------|-----------------------|---------------|----------------|---|---|--------|---|---|---|
| AN10010T2 | Black | 10 m | MAXIBLOC AN10010T2 | 3295249255237 | 13295249255234 | 1 | 1 | 3.5 kg | 30.0 cm | 17.0 cm | 10.0 cm |



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height