



Fall protection

MAXIBLOC AN10006T

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 6 metres



Specific benefits



Performance

· Certification above the maximum rated load of 100 kg: product certified at 150 kg

Applications

- Building
- Finishing works / Craftsmanship

Certifications and norms



EN360

RFU 11.062
150 KG

Protects against risks



Fall



Fall protection

MAXIBLOC AN10006T

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 6 metres

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Galvanized steel
ARA length (m)	6
ARA length (inch)	236.2206
Cable diameter (mm)	4
Included elements	Included energy absorber
Color	Black
Connector (user side)	Small hook, steel, opening 21 mm
SIZE	6 m
Benefits element	Fall indicator
Lifespan from manufacturing (years)	20
Weight (kg)	2,8
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface








Fall protection

MAXIBLOC AN10006T

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 6 metres

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN10006T	Black	6 m	MAXIBLOC AN10006T	3295249219901	13295249219908	1	1	2.8 kg	30.0 cm	17.0 cm	10.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height