



Fall protection

# AN203200ZD

## ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips



### Specific benefits



#### Hygiene

· Harnesses and textiles can be washed with neutral soap



#### Performance

· Strap with improved abrasion resistance and certified for use on sharp edges

· Certification above the maximum rated load of 100 kg; product certified at 140 kg

### Applications

- Public works
- Finishing works / Craftsmanship
- Automotive
- Storage

### Certifications and norms



#### EN355

HORIZONTAL CERTIFICATION  
RFU 11.062  
140 KG

### Protects against risks



Fall



Fall protection

# AN203200ZD

## ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips

### Standards - Details

### Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Polyester
Length (m)	2
Gate opening (mm)	55
Opening (inch)	2.1616
Lock	Automatic system
With connector	yes
Fall factor	F2
Color	Orange
Connector (user side)	Automatic lock hook, steel, opening 18mm
Ending	2 sewn thimble loops
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Length (ft)	6.5616








# AN203200ZD

## ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips

Fall protection

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN203200ZD	Orange	2 m	AN203200ZD	3295249264970	13295249264977	5	1	6.146 kg	28.4 cm	43.2 cm	14.6 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height