



Fall protection

AN213200ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances



Specific benefits



Hygiene

· Can wash harnesses and textiles with neutral soap



Performance

· Webbing with better abrasion resistance and certified against sharp edges
· Certification above maximum rated load 100kg: product certified at 140kg

Applications

- Public Works
- Finishing Works/Craftsmanship
- Automotive
- Power Energy
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG

Risk Protection



Fall



enjoy safety.



Fall protection

AN213200ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Orange
Connector 1	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,6
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616








Fall protection

AN213200ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN213200ZDD	Orange	2 m	AN213200ZDD	3295249265083	13295249265080	5	1	9.47 kg	45.0 cm	29.5 cm	18.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height