



Fall protection

# LO047150AD

## LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure



## Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

## Certifications and norms



EN354

## Protects against risks



Fall



Fall protection

# LO047150AD

## LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

### Standards - Details

### Technical details

Type of equipment	Braided rope lanyard
Composition of the main support	Polyamide
Length (m)	1,5
Rope diameter (mm)	10,5
With connector	yes
Color	White
Connector (user side)	Automatic lock hook, steel, opening 19mm
SIZE	1.50 m
Ending	2 sewn thimble loops
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	0,802
Fall arrest work situations	Restraint
Lenght (ft)	4.9213








Fall protection

# LO047150AD

## LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LO047150AD	White	1.50 m	LO047150AD	3660348006354	13660348006351	5	1	4.6 kg	14.5 cm	38.0 cm	16.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height