

PROTECTOR TETRA AN15006T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres



Certifications and norms



EN360

RFU 11.062 150 KG

Protects against risks



Specific benefits



Performance

· Certification above the maximum rated load of 100 kg: product certified at 150 kg



Easy to use

- · Automatic carabiners for secure and time-saving locking
- · Carrying handle for easy transport
- · NFC system guarantees traceability



Durability

· Impact-resistant ABS housing



Visibility

 \cdot Visual fall indicator for instant verification that the product is working properly

Applications

- Building
- Maintenance
- Chemical industry
- Petrochemical
- Storage





PROTECTOR TETRA AN15006T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Galvanized steel
ARA lenght (m)	6
ARA lenght (inch)	236.2206
Cable diameter (mm)	4
Included elements	Included energy absorber
Color	Orange
Connector (user side)	Small hook, steel, opening 21 mm
SIZE	6 m
Benefits element	Fall indicator
Lifespan from manufacturing (years)	20
Weight (kg)	5,6
Maximum load for one person (kg)	150
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface
Locking system	Inertia locking system







PROTECTOR TETRA AN15006T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres

Logistics information Reference Colour Size Designation EAN13 Box code Weight PROTECTOR TETRA AN15006T 28.0 14.0 AN15006T Orange 6 m 3295249195502 13295249195509 5.7 kg

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height