



Fall protection

MICROBLOC AN106PF

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use on platforms, for short distances



Specific benefits



Comfort

- Double swivel for optimum user tracking



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg; product certified at 140 kg



Easy to use

- NFC system guarantees traceability



Visibility

- Visual fall indicator for instant verification that the product is working properly

Applications

- Agriculture
- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)

Certifications and norms



EN360

RFU 10.060
HORIZONTAL CERTIFICATION
RFU 11.062
140 KG
RFU 11.085
F2



Fall protection

MICROBLOC AN106PF

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use on platforms, for short distances

Standards - Details

Technical details

Type of equipment	Webbing reel
Composition of the main support	Polyamide, Polyester
ARA lenght	1,8 m
ARA lenght	70.8662 inch
Fall factor	F2
Included elements	Included energy absorber
Color	Black
Lifespan from manufacturing	10 years
Weight	1,26 kg
Maximum load for one person	140 kg
Fall arrest work situations	Vertical movement on a permanent structure, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



Fall protection

MICROBLOC AN106PF

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use on platforms, for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
AN106PF	Black	1,8 m	MICROBLOC AN106PF	3295249275358	13295249275355	5	1	7.9 kg