



Fall protection

# PROTECTOR ELEVATOR TR01820U

ANTICHUTE À RAPPEL AUTOMATIQUE

20 metre self retractable fall arrester with rescue option for victim recovery



## Specific benefits



### Comfort

- Double swivel for optimum user tracking



### Performance

- Certification above the maximum rated load of 100 kg: product certified at 150 kg



### Easy to use

- End handle for easy cable winding
- Carrying handle for easy transport
- NFC system guarantees traceability



### Durability

- Impact-resistant ABS housing

## Applications

- Stavba
- Second work / craftman
- Vzdrževanje
- Kemična industrija
- Nafta in plin (pridobivanje)
- Rudarska industrija

## Certifications and norms



### EN360

RFU 11.062  
150 KG

### EN1496

CLASS A  
150 KG



Fall protection

# PROTECTOR ELEVATOR TR01820U

ANTICHUTE À RAPPEL AUTOMATIQUE

20 metre self retractable fall arrester with rescue option for victim recovery

## Standards - Details

## Technical details

Type of equipment	Cable reel, winch function
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Stainless steel
ARA lenght	20 m
ARA lenght	787.402 inch
Cable diameter	5 mm
Included elements	Included energy absorber
Color	Črna-Oranžna
Connector (user side)	Small hook, steel, opening 21 mm
Benefits element	Fall indicator
Lifespan from manufacturing	20 let
Weight	13,9 kg
Maximum load for one person	150 kg
Fall arrest work situations	Rescue and evacuation, Vertical movement, confined space
Locking system	Inertia locking system








# PROTECTOR ELEVATOR TR01820U

## RETRACTABLE FALL ARRESTERS

20 metre self retractable fall arrester with rescue option for victim recovery

Fall protection

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TR01820U	Black-Orange	20 m	PROTECTOR ELEVATOR TR01820U	3295249254704	13295249254701	1	1	14.7 kg	47.0 cm	28.0 cm	21.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height