



Fall protection

PROTECTOR ELEVATOR TR01820U

RETRACTABLE FALL ARRESTERS

20 metre self retractable fall arrester with rescue option for victim recovery



Specific benefits



Comfort

- Double swivel ensures it will maintain pursuit of user



Performance

- Certification above maximum rated load 100kg; product certified at 150kg



Ease of Use

- End handle to help wind cable
- Carry handle for easy transport
- NFC system guarantees traceability



Sustainability

- Impact resistant ABS housing

Applications

- **Building**
- **Finishing Works/Craftsmanship**
- **Maintenance**
- **Chemical Industry**
- **Oil & Gas (Extraction)**
- **Mining**

Certifications and norms



EN360

RFU 11.062
150 KG

EN1496

CLASS A
150 KG



Fall protection

PROTECTOR ELEVATOR TR01820U

RETRACTABLE FALL ARRESTERS

20 metre self retractable fall arrester with rescue option for victim recovery

Standards - Details

Technical details

Type of equipment	Cable reel, winch function
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Stainless steel
ARA lenght	20 m
ARA lenght	787.402 inch
Cable diameter (mm)	5 mm
Included elements	Energy absorber
Color	Black-Orange
Connector 1	Small hook, steel, opening 21 mm
Benefits element	Fall indicator
Lifespan from manufacturing	20 years
Weight	13,9 kg
Maximum load for one person	150 kg
Fall arrest work situations	Rescue and evacuation, Vertical movement, confined space
Locking system	Inertia locking system








PROTECTOR ELEVATOR TR01820U

RETRACTABLE FALL ARRESTERS

20 metre self retractable fall arrester with rescue option for victim recovery

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TR01820U	Black-Orange	20 m	PROTECTOR ELEVATOR TR01820U	3295249254704	13295249254701	1	1	14.7 kg	47.0 cm	28.0 cm	21.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height