



AM007

DISPOSITIFS D'ANCRAGE

Fall protection



Applications

- Kmetijstvo
- Stavba
- Second work / craftman
- Vzdrževanje
- Kemična industrija
- Rudarska industrija

Certifications and norms



EN354

EN 795

TYPE B

Protects against risks



Fall



AM007

DISPOSITIFS D'ANCRAGE

Fall protection

Standards - Details

Technical details

Type of equipment	Sling anchor
Composition of the main support	Steel
Length (m)	1
Cable diameter (mm)	8
Included elements	protective sheath
Color	Jeklo
SIZE	1 m
Ending	2 thimble ferrule loops
Lifespan from manufacturing (let)	20
Weight (kg)	0,600
Breaking Strength (Kn)	12kN
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Diameter (mm)	8
Lenght (ft)	3.2808








Fall protection

AM007

ANCHORAGE DEVICES

Steel sling covered with a protective sheath, designed for structures with sharp angles

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AM007	Steel	1 m	AM007	3660348006149	13660348006146	5	1	3.2 kg	46.5 cm	28.0 cm	12.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height