



Protipádová ochrana

TRA32

OCHRANA PŘI PRÁCI VE VÝŠKÁCH A ZÁCHRANA Z ÚZKÝCH PROSTOR

Hliníkový stativ do 3 metrů, se 2 nosnými deskami, lehký, se snadnou instalací, pro všechny druhy práce ve stísněných prostorech



Použití

- Budova
- Dokončovací stavební práce / řemesla
- Údržba
- Chemický průmysl
- Ropa & plyn (těžba)
- Těžební průmysl

Certifikace a normy



EN 795

TYP B

TS16415

3

Chrání před riziky



Pád



Protipádová ochrana

TRA32

OCHRANA PŘI PRÁCI VE VÝŠKÁCH A ZÁCHRANA Z ÚZKÝCH PROSTOR

Hliníkový stativ do 3 metrů, se 2 nosnými deskami, lehký, se snadnou instalací, pro všechny druhy práce ve stísněných prostorech

Podrobnosti - Normy

Technické detaily

Typ zařízení	Teleskopický stativ
Kotevní zařízení	Stativ
Složení hlavního držáku	Hliník
Max. délka (m)	3,02
Min. délka (m)	1,75
Barva	Hliníková
SIZE	Nastavitelná
Životnost od výroby (let)	20
Váha (kg) (kg)	22,2
Rozvor (m)	2,62
Maximální počet uživatelů	3
Možnosti zabezpečení práce ve výškách	Záchrana a evakuace, Vertikální pohyb v uzavřeném prostoru








Fall protection

TRA32

FALL ARREST AND RESCUE, CONFINED SPACE

Aluminium tripod up to 3 metres, with 2 support plates, light and easy to install for all types of work in confined spaces

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TRA32	Aluminium-coloured	Adjustable	TRA32	3295249194178	13295249194175	1	1	29.35 kg	212.0 cm	24.0 cm	29.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height