

LV102150 ANCHORAGE DEVICES

Fall protection

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 1,5m



Certifications and norms

CE

EN354

EN 795

TYPE B

Risk Protection





Specific benefits



· High webbing tenacity thanks to its weave and width

Applications

- Agriculture
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Oil & Gas (Extraction)



Edit 31/10/2024 www.deltaplus-usa.com



LV102150

ANCHORAGE DEVICES

the harness's D-ring - 1,5m

Fall protection

Standards - Details

Technical details

Anchorage strap that can also be used as an evacuation strap, to be connected to

Type of equipment	Extension strap in high tenacity polyester with D-ring.
Composition of the main support	Steel, Polyester
Length (m)	1,5
Width (inch)	1.7685
Width (mm)	45
Color	Black-Orange
SIZE	1.50 m
Ending	Loop with shrinkage
Lifespan from manufacturing (years)	10
Weight (kg)	0,277
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Lenght (ft)	4.9213



enjoy so



LV102150 ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 1,5m

Fall protection

Logistics information												
Reference	Colour	Size	Designation	EAN13	Box code		1	Weight				
LV102150	Black-Orange	1.50 m	LV102150	3660348006323	13660348006320	15	1	4.94 kg	44.0 cm	28.0 cm	15.0 cm	



ſ

Multiple sales

Minimum sales

Box Width

👕 Box Depth

🗍 Box Height



enjoy sa

21/11/2024 www.deltaplus.eu