



L0030150

LANYARDS

1.5 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining



Certifications and norms



EN354

EN 795

TYPE B

Protects against risks



Fall



LO030150

LANYARDS

1.5 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

Standards - Details

Technical details

Type of equipment	Webbing lanyard and anchorage point
Composition of the main support	Polyester
Length (m)	1,5
Width (inch)	0.9825
Width (mm)	25
Color	Black-Orange
SIZE	1.50 m
Ending	2 sewn loops
Lifespan from manufacturing (years)	10
Weight (kg)	0,187
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Lenght (ft)	4.9213








LO030150

LANYARDS

1.5 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LO030150	Black-Orange	1.50 m	LO030150	3295249215866	13295249215863	15	1	2.8 kg	22.0 cm	31.0 cm	16.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height