



L0030150

LANYARDS

1.5 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection



Applications

- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Oil & Gas (Extraction)
- Mining

Certifications and norms



EN354

EN 795

TYPE B



LO030150

LANYARDS

1.5 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

Standards - Details

Technical details

Type of equipment	Lanyard and anchorage point in tubular strap
Composition of the main support	Polyester
Length	1,5 m
Width	0.9825 inch
Width	25 mm
Color	Black-Orange
SIZE	1.50 m
Ending	2 sewn loops
Lifespan from manufacturing	10 years
Weight	0,187 kg
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Lenght	4.9213 ft








LO030150

LANYARDS

1.5 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LO030150	Black-Orange	1.50 m	LO030150	3295249215866	13295249215863	15	1	2.8 kg	22.0 cm	31.0 cm	16.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height