



Fall protection

LYNX HAR35R

FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers



Specific benefits



Comfort

- 3D comfort foam integrated into harness that provides comfort and breathability for prolonged use
- Thermoformed belt provides lumbar support and optimal comfort



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg: product certified at 150kg



Ease of Use

- Ergonomic design facilitates user movement
- NFC system guarantees traceability

Applications

- **Public Works**
- **Finishing Works/Craftsmanship**
- **Chemical Industry**
- **Automotive**
- **Oil & Gas (Extraction)**
- **Mining**

Certifications and norms



EN361

150 KG

EN813

150 KG

EN358



Fall protection

LYNX HAR35R

FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

Standards - Details

Technical details

Type of equipment	Fall arrest, support and suspension harnesses
Composition of the main support	Aluminum, Polyester
Fastening	Buckles
Number of fall arrest attachment points	2
Number of total suspension points	1
Number of total holding attachment points	2
Buckles	Automatic loop
Anti-fall point	Dorsal, Sternal
Suspension point	Ventral
Holding point	Belt
Color	Grey-Yellow
Comfort elements	"Soft padding" on shoulders and thigh strap, Thermocompressed back and shorts
Size	S/M/L, XL/XXL
Benefits element	Comfort, Fall indicator
Lifespan from manufacturing	10 years
Number of non-removable buckles	4
Weight	2,5 kg
Number of manual buckles	2
Number of automatic loops	2
Number of fall arrest anchorage points	2
Padding	Back, Belt, Leg
Sternal	1
Dorsal	1
Use	120° rotation
Fall arrest work situations	Vertical movement on a permanent structure, Work positioning, Movement on lifeline, Restraint, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical

Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection








Fall protection

LYNX HAR35R


FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
HAR35RPT	Grey-Yellow	S	LYNX HAR35R	3295249270216	13295249270213	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm
HAR35RGT	Grey-Yellow	M/L	LYNX HAR35R	3295249265304	13295249265301	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm
HAR35RXX	Grey-Yellow	XL/XXL	LYNX HAR35R	3295249265311	13295249265318	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height