



AN203100ZZ

LONGES ABSORBEUR D'ÉNERGIE

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Performance

· Strap with improved abrasion resistance and certified for use on sharp edges

· Certification above the maximum rated load of 100 kg; product certified at 140 kg

Applications

- Javna dela
- Second work / craftman
- Avtomobilska
- Shranjevanje

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG

Protects against risks



Fall



AN203100ZZ

LONGES ABSORBEUR D'ÉNERGIE

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Polyester
Length (m)	1
With connector	yes
Color	Oranžna
Connector (user side)	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connector (structure side)	Self-locking hook, steel, opening 20 mm, Crochet à verrouillage automatique, acier, ouverture 19 mm
Lifespan from manufacturing (let)	10
Weight (kg)	0,600
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	3.2808








Fall protection

AN203100ZZ

ENERGY ABSORBING LANYARDS

Compact energy absorbing lanyard made of high impact webbing to reduce the user's draught

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN203100ZZ	Orange	1 m	AN203100ZZ	3295249264963	13295249264960	5	1	3.9 kg	44.0 cm	28.0 cm	12.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height