



AN203200ZZ

LONGES ABSORBEUR D'ÉNERGIE

Fall protection



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Strap with improved abrasion resistance and certified for use on sharp edges
- Certification above the maximum rated load of 100 kg; product certified at 140 kg

Applications

- Javna dela
- Second work / craftman
- Avtomobilska
- Shranjevanje

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG

Protects against risks



Fall



AN203200ZZ

LONGES ABSORBEUR D'ÉNERGIE

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Polyester
Length (m)	2
With connector	yes
Color	Oranžna
Connector (user side)	Automatic lock hook, steel, opening 18mm
Ending	2 sewn thimble loops
Connector (structure side)	Crochet à verrouillage automatique, acier, ouverture 19 mm
Lifespan from manufacturing (let)	10
Weight (kg)	0,668
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616








AN203200ZZ

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN203200ZZ	Orange	2 m	AN203200ZZ	3295249264987	13295249264984	5	1	4.32 kg	28.6 cm	44.0 cm	14.4 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height