

AN203200ZZ

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips



Specific benefits



Hygiene

· Can wash harnesses and textiles with neutral soap



Performance

- · Webbing with better abrasion resistance and certified against sharp edges
- · Certification above maximum rated load 100kg: product certified at 140kg

Applications

- Public Works
- Finishing Works/Craftsmanship
- Automotive
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION RFU 11.062 140 KG

Risk Protection









AN203200ZZ

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Polyester
Length (m)	2
With connector	yes
Color	Orange
Connector 1	Automatic lock hook, steel, opening 16mm
Ending	2 sewn thimble loops
Connectors (structure side)	Automatic lock hook, steel, opening 19mm
Lifespan from manufacturing (years)	10
Weight (kg)	0,668
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616







AN203200ZZ

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips

Logistics information Reference Colour Size Designation EAN13 Box code Image: Colour with the property of the pro

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height