



# AN208R2AD

## LONGES ABSORBEUR D'ÉNERGIE

Fall protection



### Specific benefits



#### Hygiene

· Harnesses and textiles can be washed with neutral soap



#### Performance

· Certification above the maximum rated load of 100 kg: product certified at 140 kg  
· Strap with improved abrasion resistance and certified for use on sharp edges

### Applications

- Javna dela
- Second work / craftman
- Avtomobilska
- Shranjevanje

### Certifications and norms



#### EN355

HORIZONTAL CERTIFICATION  
RFU 11.062  
140 KG

### Protects against risks



Fall



# AN208R2AD

## LONGES ABSORBEUR D'ÉNERGIE

Fall protection

### Standards - Details

### Technical details

Type of equipment	Braided rope lanyard
Composition of the main support	Galvanized steel, Polyester
Length (m)	2
Adjustment	Adjustable by means of a reducing loop on the rope
Rope diameter (mm)	12
With connector	yes
Color	Bela-Črna
Connector (user side)	Automatic lock hook, steel, opening 19mm
SIZE	1.50 to 2 m
Benefits element	Leading edge
Ending	1 loop sewn thimble
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Lifespan from manufacturing (let)	10
Weight (kg)	1,27
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616








Fall protection

# AN208R2AD

## ENERGY ABSORBING LANYARDS

Adjustable energy absorbing lanyard allowing the length of the lanyard to be adjusted and therefore reducing the air draft, if necessary

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN208R2AD	White-Black	1.50 to 2 m	AN208R2AD	3295249265052	13295249265059	5	1	7.6 kg	18.0 cm	29.4 cm	45.2 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height