



AN213100ZDD

LONGES ABSORBEUR D'ÉNERGIE

Fall protection



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Strap with improved abrasion resistance and certified for use on sharp edges
- Certification above the maximum rated load of 100 kg; product certified at 140 kg

Applications

- Javna dela
- Second work / craftman
- Avtomobilska
- Energija
- Shranjevanje

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG

Protects against risks



Fall



AN213100ZDD

LONGES ABSORBEUR D'ÉNERGIE

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	1
With connector	yes
Color	Oranžna
Connector (user side)	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (let)	10
Weight (kg)	1,3
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	3.2808








Fall protection

AN213100ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN213100ZDD	Orange	1 m	AN213100ZDD	3295249265076	13295249265073	5	1	8.58 kg	54.0 cm	21.5 cm	15.5 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height