



Fall protection

# AN213200ZZZ

## ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances



### Specific benefits



#### Hygiene

· Can wash harnesses and textiles with neutral soap



#### Performance

· Webbing with better abrasion resistance and certified against sharp edges  
· Certification above maximum rated load 100kg: product certified at 140kg

### Applications

- Public Works
- Finishing Works/Craftsmanship
- Automotive
- Power Energy
- Storage

### Certifications and norms



#### EN355

HORIZONTAL CERTIFICATION  
RFU 11.062  
140 KG

### Risk Protection



Fall



*enjoy safety.*



Fall protection

# AN213200ZZZ

## ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances

### Standards - Details

### Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Orange
Connector 1	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connectors (structure side)	Automatic lock hook, steel, opening 19mm
Lifespan from manufacturing (years)	10
Weight (kg)	0,668
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Length (ft)	6.5616








Fall protection

# AN213200ZZZ

## ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN213200ZZZ	Orange	2 m	AN213200ZZZ	3295249265090	13295249265097	5	1	5.63 kg	22.0 cm	31.0 cm	16.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height