



Fall protection

AN218R2ADD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard with adjustable length allowing the length to be adjusted and therefore reducing the air draft, if necessary



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Performance

· Certification above the maximum rated load of 100 kg: product certified at 140 kg
· Strap with improved abrasion resistance and certified for use on sharp edges

Applications

- Public works
- Finishing works / Craftsmanship
- Automotive
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG

Protects against risks



Fall



Fall protection

AN218R2ADD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard with adjustable length allowing the length to be adjusted and therefore reducing the air draft, if necessary

Standards - Details

Technical details

Type of equipment	Braided rope lanyard
Composition of the main support	Steel, Polyamide, Polyester
Length (m)	2
Adjustment	Adjustable by means of a reducing loop on the rope
Rope diameter (mm)	12
With connector	yes
Color	White-Black
Connector (user side)	Automatic lock hook, steel, opening 19mm
SIZE	1.50 to 2 m
Ending	1 loop sewn thimble
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,97
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616








Fall protection

AN218R2ADD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard with adjustable length allowing the length to be adjusted and therefore reducing the air draft, if necessary

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN218R2ADD	White-Black	1.50 to 2 m	AN218R2ADD	3295249265106	13295249265103	5	1	11.54 kg	29.5 cm	45.5 cm	28.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height