



Fall protection

AN235200AD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg; product certified at 140 kg
- Strap with improved abrasion resistance and certified for use on sharp edges



Easy to use

- Automatic carabiners for secure and time-saving locking
- NFC system guarantees traceability

Applications

- Public works
- Finishing works / Craftsmanship
- Chemical industry
- Automotive
- Oil & Gas (extraction)
- Mining

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG

Protects against risks



Fall



Fall protection

AN235200AD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Standards - Details

Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Black-Orange
Connector (user side)	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,07
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616








Fall protection

AN235200AD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN235200AD	Black-Orange	1.40 2 m	AN235200AD	3295249265120	13295249265127	5	1	6.104 kg	28.8 cm	43.2 cm	14.8 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height