



# AN218R2ADD

## LONGES ABSORBEUR D'ÉNERGIE

Fall protection



### Specific benefits



#### Hygiene

· Harnesses and textiles can be washed with neutral soap



#### Performance

· Certification above the maximum rated load of 100 kg; product certified at 140 kg  
· Strap with improved abrasion resistance and certified for use on sharp edges

### Applications

- Javna dela
- Second work / craftman
- Avtomobilska
- Shranjevanje

### Certifications and norms



#### EN355

HORIZONTAL CERTIFICATION  
RFU 11.062  
140 KG

### Protects against risks



Fall



# AN218R2ADD

## LONGES ABSORBEUR D'ÉNERGIE

Fall protection

### Standards - Details

### Technical details

Type of equipment	Braided rope lanyard
Composition of the main support	Steel, Polyamide, Polyester
Length (m)	2
Adjustment	Adjustable by means of a reducing loop on the rope
Rope diameter (mm)	12
With connector	yes
Color	Bela-Črna
Connector (user side)	Automatic lock hook, steel, opening 19mm
SIZE	1.50 to 2 m
Ending	1 loop sewn thimble
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (let)	10
Weight (kg)	1,97
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616








Fall protection

# AN218R2ADD

## ENERGY ABSORBING LANYARDS

Energy absorbing lanyard with adjustable length allowing the length to be adjusted and therefore reducing the air draft, if necessary

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN218R2ADD	White-Black	1.50 to 2 m	AN218R2ADD	3295249265106	13295249265103	5	1	11.54 kg	29.5 cm	45.5 cm	28.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height