



Fall protection

# AN235200AD

## ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement



### Specific benefits



#### Hygiene

- Can wash harnesses and textiles with neutral soap



#### Performance

- Certification above maximum rated load 100kg; product certified at 140kg
- Webbing with better abrasion resistance and certified against sharp edges



#### Ease of Use

- Automatic carabiners for secure locking and time saving
- NFC system guarantees traceability

### Applications

- Public Works
- Finishing Works/Craftsmanship
- Chemical Industry
- Automotive
- Oil & Gas (Extraction)
- Mining

### Certifications and norms



EN355

HORIZONTAL CERTIFICATION  
RFU 11.062  
140 KG

### Risk Protection



Fall



Fall protection

# AN235200AD

## ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

### Standards - Details

### Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Black-Orange
Connector 1	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connectors (structure side)	1 automatic lock hook, steel, opening 55mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,07
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616








Fall protection

# AN235200AD

## ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN235200AD	Black-Orange	1.40 2 m	AN235200AD	3295249265120	13295249265127	5	1	6.104 kg	28.8 cm	43.2 cm	14.8 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height