



Fall protection

LV102050

ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 0,5m



Specific benefits



Durability

· High webbing tenacity thanks to its weave and width

Applications

- Agriculture
- Finishing works / Craftsmanship
- Chemical industry
- Automotive
- Oil & Gas (extraction)
- Mining

Certifications and norms



EN354

EN 795

TYPE B

Protects against risks



Fall



Fall protection

LV102050

ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 0,5m

Standards - Details

Technical details

Type of equipment	Extension strap in high tenacity polyester with D-ring.
Composition of the main support	Steel, Polyester
Strap width (mm)	45mm
Length (m)	0,5
Width (inch)	1.7685
Width (mm)	45
Color	Black-Orange
SIZE	0,50 m
Ending	Loop with shrinkage
Lifespan from manufacturing (years)	10
Weight (kg)	0,300
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Lenght (ft)	1.6404








Fall protection

LV102050

ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 0,5m

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LV102050	Black-Orange	0,50 m	LV102050	3295249204631	13295249204638	15	1	3.6 kg	31.0 cm	22.0 cm	16.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height