



Fall protection

LO147150CDD

LANYARDS

1.5 metre double lanyard with large opening connector, for maximum versatility and connection to any type of structure



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

Certifications and norms



EN354

Protects against risks



Fall



LO147150CDD

LANYARDS

Fall protection

1.5 metre double lanyard with large opening connector, for maximum versatility and connection to any type of structure

Standards - Details

Technical details

Type of equipment	Braided rope
Composition of the main support	Polyamide
Length (m)	1,5
Rope diameter (mm)	10,5
With connector	yes
Color	White
Connector (user side)	Screw carabiner, steel, opening 18mm
SIZE	1.50 m
Ending	1 loop sewn thimble
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,4
Fall arrest work situations	Restraint
Lenght (ft)	4.9213



Fall protection

LO147150CDD

LANYARDS

1.5 metre double lanyard with large opening connector, for maximum versatility and connection to any type of structure

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LO147150CDD	White	1.50 m	LO147150CDD	3660348006361	13660348006368	5	1	7.5 kg	20.6 cm	53.5 cm	14.5 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height