



Protezione anticaduta

LO147150CDD

FUNI

Doppio cordino da 1,5 metri con connettore ad ampia apertura per una massima versatilità e per il collegamento a qualsiasi tipo di struttura.



Campi di utilizzo

- Edificio
- Finitura / artigiani
- Manutenzione
- Industria chimica
- Petrolio e gas minerario (estrazione)
- Industria mineraria

Certificazioni e norme



EN354



LO147150CDD

FUNI

Protezione anticaduta

Doppio cordino da 1,5 metri con connettore ad ampia apertura per una massima versatilità e per il collegamento a qualsiasi tipo di struttura.

Dettagli - Norme

Dettagli tecnici

Tipo di attrezzatura	Corda intrecciata
Composizione del supporto principale	Poliammide
Lunghezza	1,5 m
Diametro della fune	10,5 mm
Con connettore	sì
Colore	Bianco
Connettore (lato utilizzatore)	Moschettone a vite, acciaio, apertura 18 mm
SIZE	1,50 m
Terminazione	1 occhiello cucito
Connettore (lato struttura)	2 connettori a chiusura automatica, acciaio, apertura 55 mm
Durata di vita a partire dalla data di fabbricazione	10 anni
Peso (kg)	1,4 kg
Situazioni di lavoro	Trattenuta
Lunghezza	4.9213 ft








Fall protection

LO147150CDD

LANYARDS

1.5 metre double lanyard with large opening connector, for maximum versatility and connection to any type of structure

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LO147150CDD	White	1.50 m	LO147150CDD	3660348006361	13660348006368	5	1	7.5 kg	20.6 cm	53.5 cm	14.5 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height