



Fall protection

L0007150CD

LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Oil & Gas (extraction)
- Mining
- Power Energy

Certifications and norms



EN354



Fall protection

L0007150CD

LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Standards - Details

Technical details

| | |
|---------------------------------|---|
| Type of equipment | Twisted rope |
| Composition of the main support | Polyamide |
| Length | 1,5 m |
| Rope diameter | 12 mm |
| With connector | yes |
| Color | White |
| Connector (user side) | Screw carabiner, steel, opening 18mm |
| SIZE | 1.50 m |
| Ending | 2 sewn thimble loops |
| Connector (structure side) | 1 automatic lock hook, steel, opening 55 mm |
| Lifespan from manufacturing | 10 years |
| Weight | 0,850 kg |
| Fall arrest work situations | Restraint |



Fall protection

LO007150CD

LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Logistics information

| Reference | Colour | Size | Designation | EAN13 | Box code | | | Weight | | | |
|------------|--------|--------|-------------|---------------|----------------|----|---|---------|---------|---------|---------|
| LO007150CD | White | 1.50 m | LO007150CD | 3660348006347 | 13660348006344 | 15 | 1 | 14.3 kg | 29.0 cm | 44.2 cm | 24.4 cm |

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height