



Fall protection

# L0007150CD

## LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure



## Applications

- Building
- Finishing Works/Craftsmanship
- Maintenance
- Oil & Gas (Extraction)
- Mining
- Power Energy

## Certifications and norms



EN354



# L0007150CD

## LANYARDS

Fall protection

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

### Standards - Details

### Technical details

Type of equipment	Twisted rope
Composition of the main support	Polyamide
Length	1,5 m
Rope diameter	12 mm
With connector	yes
Color	White
Connector 1	Screw carabiner, steel, opening 18mm
SIZE	1.50 m
Ending	2 sewn thimble loops
Connectors (structure side)	1 automatic lock hook, steel, opening 55mm
Lifespan from manufacturing	10 years
Weight	0,850 kg
Fall arrest work situations	Restraint








Fall protection

# LO007150CD

## LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LO007150CD	White	1.50 m	LO007150CD	3660348006347	13660348006344	15	1	14.3 kg	29.0 cm	44.2 cm	24.4 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height