

PROTECTOR ROUND AN12015T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 15 metres



Certifications and norms



EN 362

EN360

RFU 11.062 150 KG

Protects against risks



Specific benefits



Performance

· Certification above the maximum rated load of 100 kg: product certified at 150 kg



Durability

· Impact-resistant ABS housing

Applications

- Building
- Maintenance
- Chemical industry
- Petrochemical
- Storage





PROTECTOR ROUND AN12015T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 15 metres

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Galvanized steel
ARA lenght (m)	15
ARA lenght (inch)	590.5515
With connector	yes
Color	Orange
SIZE	15 m
Benefits element	Fall indicator
Lifespan from manufacturing (years)	20
Weight (kg)	6,29
Maximum load for one person (kg)	150
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface







PROTECTOR ROUND AN12015T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 15 metres

Logistics information Reference Colour Size Designation EAN13 Box code Weight Weight

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height