

PROTECTOR ROUND AN12006T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres



Certifications and norms



EN360

RFU 11.062 150 KG

Protects against risks



Specific benefits



Performance

· Certification above the maximum rated load of 100 kg: product certified at 150 kg



Easy to use

- · Automatic carabiners for secure and time-saving locking
- · Carrying handle for easy transport



Durability

· Impact-resistant ABS housing



Visibility

 \cdot Visual fall indicator for instant verification that the product is working properly

Applications

- Building
- Maintenance
- Chemical industry
- Petrochemical
- Storage







PROTECTOR ROUND AN12006T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Galvanized steel
ARA lenght (m)	6
ARA lenght (inch)	236.2206
Color	Orange
SIZE	6 m
Benefits element	Fall indicator
Weight (kg)	5,7
Maximum load for one person (kg)	150
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface
Locking system	Inertia locking system







PROTECTOR ROUND AN12006T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres

Logistics information Reference Colour Size Designation EAN13 Box code Weight Weight

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height