



Fall protection

# EXA22

## WORK POSITIONING SYSTEMS

Adjustable work positioning strap lanyard via reducer. Length up to 1.80 m. 2 connectors



### Specific benefits



#### Hygiene

· Harnesses and textiles can be washed with neutral soap



#### Easy to use

· NFC system guarantees traceability



#### Durability

· High webbing tenacity thanks to its weave and width



#### Visibility

· Visual fall indicator for instant verification that the product is working properly

### Certifications and norms

ANSI Z359.3-2017

### Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Heavy industry
- Light industry
- Maintenance

### Protects against risks



Fall



Fall protection

# EXA22

## WORK POSITIONING SYSTEMS

Adjustable work positioning strap lanyard via reducer. Length up to 1.80 m. 2 connectors

### Standards - Details

### Technical details

Type of equipment	Work positioning system
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Black-Yellow
Connector (user side)	Small hook, steel, opening 21 mm
Connector (structure side)	Small hook, steel, opening 21 mm
Lifespan from manufacturing (years)	10
Weight (kg)	0.5
Type of packaging	Pack of 5
Fall arrest work situations	Work positioning, Restraint
Length (ft)	6.5616



Fall protection

# EXA22


## WORK POSITIONING SYSTEMS

Adjustable work positioning strap lanyard via reducer. Length up to 1.80 m. 2 connectors

### Logistics information


Reference	Colour	Size	Designation	EAN13	Box code			Weight			
-----------	--------	------	-------------	-------	----------	---	---	--------	---	---	---

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height