



AN245200CDD

ENERGY ABSORBING LANYARDS

Fall protection



Applications

- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Oil & Gas (Extraction)
- Mining

Certifications and norms



Risk Protection



Fall



AN245200CDD

ENERGY ABSORBING LANYARDS

Fall protection

Standards - Details

Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
Color	Black-Orange
Connector 1	Screw carabiner, steel, opening 18mm
SIZE	1.40 to 2 m
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Lifespan from manufacturing (years)	10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616








AN245200CDD

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN245200CDD	Black-Orange	1.40 2 m	AN245200CDD	3295249194222	13295249194229	5	1	9.198 kg	29.4 cm	43.4 cm	15.2 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height