



AN240ADD

LONGES ABSORBEUR D'ÉNERGIE

Fall protection



Specific benefits



Comfort

- Elastic strap lanyard for easy movement and safety



Hygiene

- Harnesses and textiles can be washed with neutral soap



Easy to use

- Automatic carabiners for secure and time-saving locking
- NFC system guarantees traceability

Certifications and norms



EN355

Applications

- Javna dela
- Kemična industrija
- Avtomobilska
- Petrokemija
- Energija
- Shranjevanje



AN240ADD

LONGES ABSORBEUR D'ÉNERGIE

Fall protection

Standards - Details

Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Steel, Polyester
Length	2 m
With connector	yes
Color	Črna
Connector (user side)	Automatic lock hook, steel, opening 19mm
Ending	2 thimble ferrule loops
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing	10 let
Weight	1,9 kg
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght	6.5616 ft








AN240ADD

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN240ADD	Black	1.40 2 m	AN240ADD	3295249172008	13295249172005	5	1	7.2 kg	27.0 cm	31.4 cm	40.6 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height