



# AN240ADD

## ENERGY ABSORBING LANYARDS

Fall protection



### Specific benefits



#### Comfort

- Elastic webbing lanyard for easy movement and safety



#### Hygiene

- Can wash harnesses and textiles with neutral soap



#### Ease of Use

- Automatic carabiners for secure locking and time saving
- NFC system guarantees traceability

### Applications

- Public Works
- Chemical Industry
- Automotive
- Petrochemical
- Power Energy
- Storage

### Certifications and norms



EN355

### Risk Protection



Fall



# AN240ADD

## ENERGY ABSORBING LANYARDS

Fall protection

### Standards - Details

### Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Black
Connector 1	Automatic lock hook, steel, opening 19mm
Ending	2 thimble ferrule loops
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,9
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616








# AN240ADD

## ENERGY ABSORBING LANYARDS

Fall protection

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN240ADD	Black	1.40 2 m	AN240ADD	3295249172008	13295249172005	5	1	7.2 kg	27.0 cm	31.4 cm	40.6 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height