



MEDBLOC AN13006C

RETRACTABLE FALL ARRESTERS

Fall protection



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Easy to use

· NFC system guarantees traceability



Visibility

· Visual fall indicator for instant verification that the product is working properly

Applications

- Building
- Maintenance
- Oil & Gas (extraction)
- Power Energy
- Storage

Certifications and norms



EN360

RFU 10.060
HORIZONTAL CERTIFICATION
RFU 11.062
128 KG

Protects against risks



Fall



MEDBLOC AN13006C

RETRACTABLE FALL ARRESTERS

Fall protection

Standards - Details

Technical details

| | |
|----------------------------------|--|
| Type of equipment | Webbing reel |
| Composition of the main support | ABS (Acrylonitrile Butadiene Styrene), Polyester |
| Strap width (mm) | 25 |
| ARA length (m) | 6 |
| ARA length (inch) | 236.2206 |
| Color | Black |
| SIZE | 6 m |
| Weight (kg) | 1,6 |
| Maximum load for one person (kg) | 128 |
| Fall arrest work situations | Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface |








MEDBLOC AN13006C

RETRACTABLE FALL ARRESTERS

Fall protection

Logistics information

| Reference | Colour | Size | Designation | EAN13 | Box code |  |  | Weight |  |  |  |
|-----------|--------|------|------------------|---------------|----------------|---|---|---------|---|---|---|
| AN13006C | Black | 6 m | MEDBLOC AN13006C | 3295249187835 | 13295249187832 | 5 | 1 | 9.33 kg | 46.0 cm | 22.0 cm | 21.0 cm |



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height